

**Section 1: IDENTIFICATION****Product details:****Trade name:** Clear Pour Monomer**Chemical name:** Methyl Methacrylate**Application of the substance / the preparation:** Manufacture of dental prosthesis**Uses Advised Against:** Non-dental use**Manufacturer/Supplier:**Fricke Dental International, Inc.
165 Roma Jean Parkway
Streamwood, IL 60107 U.S.A.
Telephone: (630) 540-1900**Emergency Information:**

(800)535-5053 (Infotrac)

Section 2: HAZARDS IDENTIFICATION**Hazard classification:**

Highly Flammable Liquid (Category 2)

Acute toxicity, Oral, Category 4 (OSHA), Category 5 (UN Purple Book GHS)

Acute toxicity, Dermal, Category 4 (OSHA), Category 5 (UN Purple Book GHS)

Acute toxicity, Inhalation, Category 4 (OSHA), Category 5 (UN Purple Book GHS)

Eye irritation (Category 2B)

Labeling Pictogram/Symbol:**Signal word:**

Danger

Hazard statement(s)

H225	Highly flammable liquid and vapor.
H303	May be harmful if swallowed.
H315	May cause skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye damage.
H335	May cause respiratory irritation.

Precautionary statement(s)

P202	Do not handle until all safety precautions have been read and understood.
P234	Keep only in original container.
P235+P410	Keep cool. Protect from sunlight.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.



Section 2: HAZARDS IDENTIFICATION (Continued...)

P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330	IF SWALLOWED: Rinse mouth.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	If exposed or concerned: Get medical advice attention.
P312	Call a poison center or doctor if you feel unwell.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Characterization:

Description:

CAS #	Name	Hazard Classification	%
80-62-6	Methyl Methacrylate (MMA)	H225 Highly flammable liquid and vapor. H303 May be harmful if swallowed. H315 May cause skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye damage. H335 May cause respiratory irritation.	>95%
97-90-5	Ethylene Glycol Dimethacrylate	H225 Highly flammable liquid and vapor. H303 May be harmful if swallowed. H315 May cause skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye damage. H335 May cause respiratory irritation.	<10%
99-97-8	Dimethyl p Toluidine	H301 Toxic if swallowed. H311 Toxic in contact with skin. H331 Toxic if inhaled. H402 Harmful to aquatic life. H413 May cause long-lasting harmful effects to aquatic life.	< 1%

Section 4: FIRST-AID MEASURES

Inhalation: Remove to fresh air. Get medical attention if discomfort persists.**Skin:** Immediately wash with water and soap. Rinse thoroughly. If irritation occurs, consult a doctor.**Eye:** Flush with plenty of water for at least 15 minutes. Seek medical advice.**Ingestion:** If swallowed, DO NOT induce vomiting, immediately give two glasses of water, or activated charcoal slurry. Seek immediate medical advice. Never give anything by mouth to an unconscious person.



Section 5: FIRE-FIGHTING MEASURES

Suitable Extinguishing Media:

CO₂, extinguishing powder, dry chemical, water fog (by trained personnel) in flooding amounts.

Approx. flammable limit by % volume in air:

LEL: 2.1 % UEL: 12.5%

Advice for Firefighters:

Wear respirator-MSHA/NIOSH approved or equivalent, self-contained breathing apparatus.

Use cold water spray to cool containers. Heat can cause containers to rupture explosively due to polymerization.

Vapors are heavier than air and may travel to the ignition source.

Section 6: ACCIDENTAL RELEASE MEASURES

Small spill

Dilute with water and mop up, or absorb with an inert dry material and place in an appropriate waste disposal container.

Large spill

Evacuate area and remove sources of ignition. Prevent skin contact and breathing vapor. Confine and remove with inert absorbent. Ventilate area. Prevent entry into sewers, basements or confined areas.

Additional information

See section 13 for disposal information.

See section 8 for information on personal protection equipment.

Section 7: HANDLING AND STORAGE

Handling

Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/vapor/spray. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as metals, acids, alkalis.

Storage

Keep in a well ventilated area. Store under 80°F (27°C). Keep container tightly closed and sealed until ready for use. Ground all equipment containing material. Avoid all possible sources of ignition (spark or flame).

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Provide good local exhaust at processing equipment controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

Eye/Face Protection: Safety goggles or chemical splash goggles.

Skin Protection: Wear impervious gloves with consideration to the product and the preparation.

Body Protection: Protective work clothing.

Respiratory Protection: Vapor respirator. Be sure to use an approved/certified respirator or equivalent.

Environmental Exposure:

Components with limit values that require monitoring at the workplace:

80-62-6 Methyl Methacrylate

PEL ()	410 mg/m ³ , 100ppm
REL ()	410 mg/m ³ , 100ppm
TLV()	Short-term value: 410 mg/m ³ , 100ppm Long-term value: 205 mg/m ³ , 50ppm

97-90-5 Ethylene Glycol Dimethacrylate

PEL ()	None Established
REL ()	
TLV()	

Additional Information: The lists that were valid during the creation were used as a basis.



Section 9: PHYSICAL AND CHEMICAL PROPERTIES

General Information	
Physical state and appearance	Liquid
Color	Not available
Odor	Acrid fruity odor
Change in Condition	
Approx. boiling point	101°C @ 760mm Hg (213.8°F)
Flash Point	55°F (Open cup) (12.78°C)
Approx. auto-ignition temperature	790°F (421°C)
SADT	N/A – does not contain organic peroxides
Other	
Vapor Density	3.5 (Air = 1)
Solubility in water	1.6g / 100g
Percent Volatile	> 95%
Evaporation Rate	3 (Butyl Acetate = 1)
Flammable limits in Air, % by Volume	Lower limit: 2.1 Upper limit: 12.5

Section 10: STABILITY AND REACTIVITY

Stability

Stable. Stable at room temperature in closed containers under normal storage and handling conditions.

Conditions to Avoid

Heat and ignition sources. Contamination.

Incompatibility

Reducing and oxidizing agents. Material has strong solvent properties and can soften paint or rubber.

Hazardous Decomposition

Can yield CO, CO₂, smoke

Hazardous Polymerization

May occur

Conditions to Avoid for Hazardous Polymerization

Excessive heat (temperatures above 40°C), contamination, peroxides, amides, and other oxidizing or reducing agents.

Section 11: TOXICOLOGICAL INFORMATION

Routes of Entry

Eye contact. Inhalation. Ingestion.

Toxicity to Animals

WARNING: THE LC50 VALUES HEREUNDER ARE ESTIMATED ON THE BASIS OF A 4-HOUR EXPOSURE. Acute oral toxicity (LD50): 7872 mg/kg [Rat]. Acute toxicity of the vapor (LC50): 5303.3 ppm 4 hours [Rat].

**Section 11: TOXICOLOGICAL INFORMATION (Continued...)****Chronic Effects on Humans:**

The substance is toxic to lungs, mucous membranes.

Other Toxic Effects on Humans:

Hazardous in case of skin contact (irritant), of ingestion, of inhalation. Slightly hazardous in case of skin contact (permeator).

Special Remarks on Toxicity to Animals:

Not available.

Special Remarks on Chronic Effects on Humans:

Embryotoxic and/or foetotoxic in animal.

Special Remarks on other Toxic Effects on Humans:

Not available.

Section 12: ECOLOGICAL INFORMATION**General Notes**

Avoid transfer into the environment.

Section 13: DISPOSAL CONSIDERATIONS**General Notes**

Avoid transfer into the environment. Do not allow product to reach sewage system.
Disposal must be completed according to official regulations.

Section 14: TRANSPORT INFORMATION

UN Number: 1247

Proper Shipping Name: Methyl Methacrylate Monomer, Inhibited

Hazard Class: 3

Packing Group: II

Label Statement: Flammable liquid

Section 15: REGULATORY INFORMATION**Federal and State Regulations**

SARA Title III, Section 302 (TPQ)

SARA Title III, Section 302 (RQ): Methyl Methacrylate - RQ (lbs): 1000

SARA Title III, Section 311-312: Methyl Methacrylate

SARA Title III, Section 313: Methyl Methacrylate

TSCA Section 8(b): This product contains chemicals that are on the TSCA List

Massachusetts RTK: Methyl Methacrylate

New Jersey RTK: Methyl Methacrylate

Pennsylvania RTK: Methyl Methacrylate

NON-hazardous ingredients present at a concentration of 3% or more required to be listed by Pennsylvania: NONE



Section 15: REGULATORY INFORMATION (Continued...)

California RTK: Methyl Methacrylate

Substances known to the state of California to cause cancer: NONE

Substances known to the state of California to cause birth defects or other reproductive harm: NONE

Florida RTK: Methyl Methacrylate

Minnesota RTK: Methyl Methacrylate

WHMIS (Canada)

Class B-2 Flammable liquid

Class D-2B Material causing other toxic effects

EINECS (Europe)

Hazard Symbols

Xi – Irritant

F – Flammable

Risk Phrases

R11 – Highly Flammable

R36/37/38 – Irritating to eyes, respiratory system and skin

R43 – May cause sensitization by skin contact

Safety Phrases

S2 – Keep out of the reach of children

S24 – Avoid contact with skin

S37 – Wear suitable gloves

S46 – If swallowed, seek medical advice immediately and show this container or label

HMIS (U.S.A.)

Health Hazard: 2

Fire Hazard: 3

Reactivity: 2

Personal Protection: H

National Fire Protection Association (U.S.A.)

Health: 2

Flammability: 3

Reactivity: 2

Specific Hazard:

Protective Equipment

Gloves

Lab Coat

Vapor respirator

Be sure to use an approved/certified respirator or equivalent. Wear an appropriate respirator when ventilation is inadequate.

Splash goggles

**Section 16: OTHER INFORMATION****References**

Not Available

Other Special Considerations

Not Available

Last Update/Revision Date:	01/02/17
Supersedes/Replaces:	SDS.1025.3
Revised by:	R. Tekstar

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall Fricke Companies be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if Fricke Companies has been advised of the possibility of such damages.